

Art-Nr. M101683

U-Profile

Produkteigenschaften


- sehr gut geeignet für dekorative anodische Oxidation

Technische Daten

EN 573-3, 755-2, 755-9
 Legierungs-/Werkstoffnorm EN AW-6060 (AlMgSi 0.5)
 Werkstoff Aluminium
 Zustand T66 (F22)
 Ausführung gepresst

Klassifikation

eClass 10.1 35-02-01-02
UNSPSC 11.2 30101806
eClass 11.0 35-07-02-02
eClass 12.0 35-07-02-02



Art-Nr.	a mm	b mm	t mm	R mm	r mm	L m	Gewicht/m kg/m
101177	12.0	15	2.0			6	0.205
101170	13.0	10	2.0			6	0.157
101182	15.0	15	2.0			6	0.222
101174	20.0	10	2.0			6	0.195
101200	20.0	20	2.0			6	0.302
101226	20.0	20	3.0			6	0.437
101244	20.0	25	4.0			6	0.67
101219	25.0	25	2.0			6	0.384
103035	25.0	25	3.0			6	0.573
100083	26.5	40	3.0	1.5		6	0.815
101227	30.0	15	3.0			6	0.437
101212	30.0	20	2.0			6	0.356
101233	30.0	20	3.0			6	0.518
103687	30.0	25	4.0			6	0.783
103037	30.0	30	2.0			6	0.473
101249	30.0	30	3.0			6	0.68
101235	35.0	25	2.5			6	0.544
101250	40.0	20	4.0			6	0.778
103038	40.0	25	3.0			6	0.686
101255	40.0	25	4.0		4	6	0.911
101257	40.0	30	4.0			6	0.994
101259	40.0	40	4.0			6	1.21
103040	50.0	25	2.5			6	0.635
103041	50.0	25	4.0			6	1.02
101258	50.0	30	4.0			6	1.1
103042	50.0	30	5.0		5	6	1.39
103044	50.0	40	4.0			6	1.346
103291	50.0	50	4.0			6	1.58
101262	60.0	30	4.0			6	1.238
103046	60.0	35	6.0		6	6	1.839
104415	80.0	40	4.0			6	1.67

Preise exkl. Verpackungskosten

