

N° d'art. M101655


Plaque

Données techniques

| | |
|----------------------------------|----------------------|
| Norme d'alliage & de matière | EN AW-6082 (AlMgSi1) |
| Matériau | Aluminium |
| Qualité | T651 (durci à chaud) |
| Résistance à la traction Rm min. | 275 MPa |
| Limite élastique Rp 0.2 min. | 240 MPa |
| Allongement à la rupture A5 | 6 % |
| Dureté Brinell env. | 84 HB |

Classification

| | |
|--------------------|-------------|
| eClass 10.1 | 35-02-05-01 |
| eClass 11.0 | 35-07-01-01 |
| eClass 12.0 | 35-07-01-01 |
| UNSPSC 11.2 | 30102206 |



| N° d'art. | t mm | a mm | b mm | kg/fl kg |
|-----------|-------|------|------|----------|
| 100103 | 8.0 | 1020 | 2020 | 45.987 |
| 100797 | 8.0 | 1520 | 2900 | 96.5 |
| 100105 | 10.0 | 1020 | 2020 | 57.414 |
| 100801 | 10.0 | 1520 | 2900 | 120.9 |
| 100804 | 12.0 | 1520 | 2900 | 144.7 |
| 100807 | 15.0 | 1520 | 2900 | 180.4 |
| 100808 | 20.0 | 1520 | 2900 | 240.5 |
| 100810 | 25.0 | 1520 | 2900 | 300 |
| 100813 | 30.0 | 1520 | 2900 | 359.5 |
| 104237 | 35.0 | 1520 | 2900 | 419.6 |
| 100816 | 40.0 | 1520 | 2900 | 479.4 |
| 100818 | 45.0 | 1520 | 2900 | 538.6 |
| 100820 | 50.0 | 1520 | 2900 | 598.1 |
| 105279 | 55.0 | 1520 | 2900 | 658.2 |
| 100823 | 60.0 | 1520 | 2900 | 717.7 |
| 117422 | 65.0 | 1520 | 2900 | 778.4 |
| 101336 | 70.0 | 1520 | 2900 | 837.9 |
| 100827 | 80.0 | 1520 | 2900 | 961.3 |
| 172880 | 90.0 | 1520 | 2900 | 1076.5 |
| 172881 | 100.0 | 1250 | 2500 | 854.74 |
| 200879 | 100.0 | 1520 | 2900 | 1195.5 |
| 114239 | 110.0 | 1250 | 2500 | 939.28 |
| 200882 | 110.0 | 1520 | 2900 | 1321.7 |
| 100833 | 120.0 | 1020 | 2020 | 673.17 |
| 201133 | 120.0 | 1250 | 2500 | 1021 |
| 101337 | 130.0 | 1020 | 2020 | 730.78 |
| 201073 | 140.0 | 1250 | 2500 | 1190.53 |
| 101339 | 150.0 | 1020 | 2020 | 843.94 |
| 201532 | 55.0 | 1520 | 2020 | 150.42 |
| 201533 | 60.0 | 1520 | 2020 | 203.41 |
| 201534 | 130.0 | 1250 | 2500 | 354.68 |
| 201535 | 140.0 | 1100 | 2800 | 381.72 |
| 201536 | 150.0 | 1250 | 2020 | 409.31 |
| 201537 | 75.0 | 1520 | 2900 | 204.93 |
| 201538 | 85.0 | 1520 | 2900 | 232.39 |



Prix sans frais d'emballage

